



LAND



SEA



AIR

THOR100-X3

INTEL® KABYLAKE RUGGED
SYSTEM COMPUTER



INTEL® KABYLAKE RUGGED

- Intel® Core™ i7-7600U (2 cores, 2.8 GHz)
- 2 x XR-DIMM up to 16GB
- 1 x mPCIe expansion slot
- 1 x 2.5" HDD/ SSD
- Amphenol M12 connector applied
- IP65 classify

Specifications

SYSTEM

Low Power Processor	Intel® Core™ i7-7600U Processor (4M Cache, up to 2.80 GHz) Turbo Boost Technology 2.0 , VPro and Hyper-Threading support.
Memory type	2 x XR-DIMM up to 16GB
Expansion Slot	1 x miniPCIe (1 with mSATA supported)

DISPLAY

VGA	Resolution up to 1920 x 1080 (with Innodisk EMPV-1201-W1 Display card)
-----	---

STORAGE

HDD/SDD	1 x 2.5" HDD/SSD HDD – up to 2TB Capacity SSD – up to 1TB Capacity
mSATA	Full-size mSATA- up to 512GB Capacity Rugged Industrial NAND Flash mSATA Storage w/ Rugged -40/+85°C High Capacity, optional Pre-loaded with Linux or Windows OS. 8 to 512GB Innodisk mSATA MLC SATA III 6Gb/s Flash SSD, Rated for 400 MB/sec Sequential Read ; 200 MB/sec Write Max. Vibration: 20G @7~2000Hz, Shock: 1500G @ 0.5m, MTBF: 3 million hours. 8 to 512GB Apacer mSATA MLC SATA III 6Gb/s Flash SSD, Rated for 505 MB/sec Sequential Read ; 360 MB/sec Write Max. Vibration: 15G @7~2000Hz, Shock: 50G @ 0.5m.

ETHERNET

Ethernet	1 x Intel I210-IT, 1 x Intel I218-LM Gigabit LAN Interfaces (10/100/1000Mbps)
----------	---

FRONT I/O

Button	Water Resistive Power Button with dual-color LED Backlight
X1 (COM)	12-Pin A-code Female M12 Connector (Amphenol M12A-12PMMS-SF8001)
X2 (VGA)	12-Pin A-code Female M12 Connector (Amphenol M12A-12PMMS-SF8001)
X3 (LAN)	8-Pin A-code Female M12 Connector (Amphenol M12S-04BFFB-SL7001)
X4 (LAN)	8-Pin A-code Female M12 Connector (Amphenol M12S-04BFFB-SL7001)
X5 (USB 2.0 x 2)	8-Pin A-code Female M12 Connector (Amphenol M12S-04BFFB-SL7001)

REAR I/O

DC-IN 4-Pin S-code Male M12 Connector (Amphenol M12S-04PMMS-SF8001)

POWER REQUIREMENT

Power Input	9V to 36V DC-in
Power Type	AT/ATX Mode Select by Jumper

**APPLICATIONS,
OPERATING SYSTEM**

Applications	Commercial and Military Platforms Requiring Compliance to MIL-STD-810G Embedded Computing, Process Control, Intelligent Automation and manufacturing applications where Harsh Temperature, Shock, Vibration, Altitude, Dust and EMI Conditions. Used in all aspects of the military.
Operating System	Microsoft Win 7 32/64Bit, Win 8 32/64Bit, Win 8.1 32/64Bit, Win 10 32/64Bit Ubuntu13.04, Ubuntu13.10, Ubuntu14.04, Fedora 20.

PHYSICAL

Dimension (W x D x H)	220 x 380 x 44 mm
Weight	5.5 Kg (12.11 lbs)
Chassis	Aluminum AL6061
Heatsink	Aluminum Alloy, Corrosion Resistant.
Finish	Anodic aluminum oxide (Color)
Cooling	Natural Passive Convection/Conduction. No Moving Parts.
Ingress Protection	IP65

ENVIRONMENTAL

MIL-STD-810G Test	Method 507.5, Procedure II (Temperature & Humidity) Method 516.6 Shock-Procedure V Non-Operating (Mechanical Shock) Method 516.6 Shock-Procedure I Operating (Mechanical Shock) Method 514.6 Vibration Category 24/Non-Operating (Category 20 & 24, Vibration) Method 514.6 Vibration Category 20/Operating (Category 20 & 24, Vibration) Method 501.5, Procedure I (Storage/High Temperature) Method 501.5, Procedure II (Operation/High Temperature) Method 502.5, Procedure I (Storage/Low Temperature) Method 502.5, Procedure II (Operation/Low Temperature)
-------------------	---

Method 503.5, Procedure I (Temperature shock)

ENVIRONMENTAL

Reliability	No Moving Parts; Passive Cooling. Designed & Manufactured using ISO 9001/2000 Certified Quality Program.
EMC	CE and FCC compliance
Green Product	RoHS, WEEE compliance
Operating Temp.	-40 to 70°C (ambient with air flow)
Storage Temp.	-40 to 85°C
Relative Humidity	5% to 95%, non-condensing.

Ordering Information

THOR100-X3

IP65 MIL-STD-810G Rugged Computer with Intel® Core™ i7-7600U Processor, 9V to 36V DC-in, Extended Temp -40 to 70°C

Dimension

Unit: mm

