

# HORUS422A

Embedded Server



## Safety information

### Electrical safety

- To prevent electrical shock hazard, disconnect the power cable from the electrical outlet before relocating the system.
- When adding or removing devices to or from the system, ensure that the power cables for the devices are unplugged before the signal cables are connected. If possible, disconnect all power cables from the existing system before you add a device.
- Before connecting or removing signal cables from the motherboard, ensure that all power cables are unplugged.
- Seek professional assistance before using an adapter or extension cord. These devices could interrupt the grounding circuit.
- Make sure that your power supply is set to the correct voltage in your area.
- If you are not sure about the voltage of the electrical outlet you are using, contact your local power company.
- If the power supply is broken, do not try to fix it by yourself. Contact a qualified service technician or your local distributor.

### Operation safety

- Before installing the motherboard and adding devices on it, carefully read all the manuals that came with the package.
- Before using the product, make sure all cables are correctly connected and the power cables are not damaged. If you detect any damage, contact your dealer immediately.
- To avoid short circuits, keep paper clips, screws, and staples away from connectors, slots, sockets and circuitry.
- Avoid dust, humidity, and temperature extremes. Do not place the product in any area where it may become wet.
- Place the product on a stable surface.
- If you encounter any technical problems with the product, contact your local distributor.

### Statement

- All rights reserved. No part of this publication may be reproduced in any form or by any means, without prior written permission from the publisher.
- All trademarks are the properties of the respective owners.
- All product specifications are subject to change without prior notice

**Revision History**

Revision	Date (yyyy/mm/dd)	Changes
Version 1.0	2018/01/24	Initial release

**Packing list**

- HORUS422A Fanless Rugged System**
- CD (Driver + Quick Installation Guide)**

**Ordering information**

Model Number	Description
HORUS422A	Intel® Q170 Skylake Rugged server, 12 Bays 2.5" SSD/HDD, RAID supported, Operating Temperature 5~+50°C



If any of the above items is damaged or missing, please contact your local distributor.

**Table Contents**

<b>SAFETY INFORMATION .....</b>	<b>1</b>
ELECTRICAL SAFETY .....	1
OPERATION SAFETY .....	1
<b>STATEMENT .....</b>	<b>1</b>
<b>REVISION HISTORY .....</b>	<b>2</b>
<b>PACKING LIST .....</b>	<b>2</b>
<b>ORDERING INFORMATION .....</b>	<b>2</b>
<b>TABLE CONTENTS .....</b>	<b>3</b>
<b>CHAPTER 1: PRODUCT INTRODUCTION .....</b>	<b>4</b>
1.1 KEY FEATURES .....	4
1.2 DIMENSIONS .....	5
1.3 FRONT PANEL COMPONENT .....	6
1.4 REAR PANEL COMPONENT .....	6




## Chapter 1: Product Introduction

### 1.1 Key Features


System	
CPU	Intel® 14 nm Skylake-S Intel® Core™ i7-6700TE Processor (8M Cache, 2.40/3.40 GHz)
Chipset	Intel® Q170
Memory Type	4 x XR-DIMM DDR4 up to 64GB
BIOS	AMI® BIOS
Expansion Slot	1 x PCIe x4 single slot 4 x mPCIe, 2 with mSATA support
Storage Device	2 x mSATA (mPCIe3, mPCIe4) RocketRAID 840A RAID Card 12 x 7mm SATA III 2.5" SSD/HDD
Front I/O	
Power Switch	1
System FAN Switch	1
HDD LED/Power LED	1
Console	1
USB 2.0	2
2.5" Disk Tray	12 x 2.5" (7mm) Easy swap HDD/SSD Trays
Handle	2
Rear I/O	
PSU Switch	1 <b>Notice:</b> Please turn this switch on before turn system on
Exhaust FAN	2 <b>Notice:</b> Smart FANS running when ambient temperature is over 50°C.
USB	4 x USB3.0
Ethernet	4 x RJ45 GbE LAN
DisplayPort	1
HDMI	1
Ground Screw	1
Power Input	1 x AC Inlet, 100-240 VAC
Mechanical & Environment	
Construction	Aluminum chassis with fanless design
Power Requirements	100-240 VAC
Dimension (W x H x D)	430 x 88 x 356mm (17.93" x 3.46" x 14.01")
Operating Temp.	5 to 50°C (ambient with air flow)
Storage Temp.	-20 to 70°C
Relative Humidity	5% to 95%, non-condensing

\* Specifications are subject to change without notice\*

## 1.2 Dimensions




### 1.3 Front Panel Component



1	Power LED
2	HDD LED
3	2 x USB2.0
4	1 x Console Port
5	12 x 2.5" (7mm) Easy swap HDD/SSD Trays
6	Power On/Off Switch
7	System FAN On/Off Switch

### 1.4 Rear Panel Component



1	AC-IN
2	4 x RJ45 GbE LAN
3	4 x USB3.0
4	HDMI
5	2 x System FAN
6	DisplayPort